




Twist Series

The Twist series gaskets are designed for demanding compression applications. This series can compress to material thickness and provide excellent shielding performance. Profiles include standard flat, right angle, double twist and clip-on.

T Twist		Black = inches Red = mm														
P/N	A	B	C	Finger	Pitch	Mat. Thick	Length	Fingers	Tape							
3-20T-XX-24-NTP	0.03	0.76	0.20	5.08	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	n/a
3-20T-XX-24	0.03	0.76	0.20	5.08	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	0.100
3-20T-XX-300	0.03	0.76	0.20	5.08	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	300	7620	3158	0.100
3-23T-XX-24-NTP	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	n/a
3-23T-XX-24	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	0.100
3-23T-XX-300	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.003	0.076	300	7620	3158	0.100
3-S-23T-XX-24-NTP	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.002	0.051	24	610	253	n/a
3-S-23T-XX-24	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.002	0.051	24	610	253	0.100
3-S-23T-XX-300	0.03	0.76	0.23	5.84	0.14	3.56	0.08	2.03	0.095	2.41	0.002	0.051	300	7620	3158	0.100
6-30T-XX-24-NTP	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	n/a
6-30T-XX-24	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	0.100
6-30T-XX-300	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.003	0.076	300	7620	1818	0.100
6-S-30T-XX-24-NTP	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	n/a
6-S-30T-XX-24	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	0.145
6-S-30T-XX-300	0.07	1.78	0.30	7.62	0.15	3.81	0.15	3.81	0.165	4.19	0.002	0.051	300	7620	1818	0.145
6-34T-XX-24-NTP	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	n/a
6-34T-XX-24	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	0.145
6-34T-XX-300	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.003	0.076	300	7620	1818	0.145
6-S-34T-XX-24-NTP	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	n/a
6-S-34T-XX-24	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	0.145
6-S-34T-XX-300	0.07	1.78	0.34	8.64	0.18	4.57	0.15	3.81	0.165	4.19	0.002	0.051	300	7620	1818	0.145




MOUNTING OPTIONS
 ■ Tape
 ■ Solder

XX - Select material/finish (see page 16)
 NTP = No Tape



TV Twist		Black = inches Red = mm														
P/N	A	B	C	Finger	Pitch	Mat. Thick	Length	Fingers	Tape							
3-23TV-XX-24-NTP	0.03	0.76	0.08	2.03	0.16	4.06	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	n/a
3-23TV-XX-24	0.03	0.76	0.08	2.03	0.16	4.06	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	0.100
3-23TV30-XX-24	0.03	0.76	0.08	2.03	0.30	7.62	0.08	2.03	0.095	2.41	0.003	0.076	24	610	253	0.250
3-S-23TV-XX-24-NTP	0.03	0.76	0.08	2.03	0.16	4.06	0.08	2.03	0.095	2.41	0.002	0.051	24	610	253	n/a
3-S-23TV-XX-24	0.03	0.76	0.08	2.03	0.16	4.06	0.08	2.03	0.095	2.41	0.002	0.051	24	610	253	0.100
3-S-23TV30-XX-300	0.03	0.76	0.08	2.03	0.30	7.62	0.08	2.03	0.095	2.41	0.002	0.051	300	7620	3158	0.250
6-34TV-XX-24-NTP	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	n/a
6-34TV-XX-24	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.003	0.076	24	610	146	0.145
6-34TV-XX-300	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.003	0.076	300	7620	1818	0.145
6-S-34TV-XX-24-NTP	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	n/a
6-S-34TV-XX-24	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.002	0.051	24	610	146	0.145
6-S-34TV-XX-300	0.07	1.78	0.14	3.56	0.20	5.08	0.15	3.81	0.165	4.19	0.002	0.051	300	7620	1818	0.145



MOUNTING OPTIONS
 ■ Tape

XX - Select material/finish (see page 16)
 NTP = No Tape



